

(12)

(21) **2 425 979**

(22) **26.10.2001**

(51) Int. Cl.<sup>7</sup>: **B01D 53/04, A62B 23/02,  
B01D 46/52**

(85) **11.04.2003**

(86) **PCT/US01/51336**

(87) **WO02/038249**

(30) **60/243,918 US 27.10.2000**

(71) **SCOTT TECHNOLOGIES, INC.,  
One Chagrin Highlands  
400-2000 Auburn Drive, BEACHWOOD, XX (US).**

(72) **ESTKOWSKI, CHRISTOPHER G. (US).**


(74) **RIDOUT & MAYBEE LLP**

(54) **ENSEMBLE FILTRE/CARTOUCHE**

(54) **COMBINATION FILTER/CARTRIDGE ASSEMBLY**

(57)

A filter cartridge assembly including a replendam that combines a particulate filter with an irregular shaped gas sorbent bed. Best operational practice requires that the air passing through the filter be distributed uniformly over the sorbent bed. The replendam directs the air over the surface of the larger sorbent bed utilizing vane-like structures extending from the reticulated member providing for uniform distribution.





(86) Date de dépôt PCT/PCT Filing Date: 2001/10/26  
(87) Date publication PCT/PCT Publication Date: 2002/05/16  
(85) Entrée phase nationale/National Entry: 2003/04/11  
(86) N° demande PCT/PCT Application No.: US 2001/051336  
(87) N° publication PCT/PCT Publication No.: 2002/038249  
(30) Priorité/Priority: 2000/10/27 (60/243,918) US

(51) Cl.Int.<sup>7</sup>/Int.Cl.<sup>7</sup> B01D 53/04, A62B 23/02, B01D 46/52


(71) Demandeur/Applicant:  
SCOTT TECHNOLOGIES, INC., US

(72) Inventeur/Inventor:  
ESTKOWSKI, CHRISTOPHER G., US

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : ENSEMBLE FILTRE/CARTOUCHE

(54) Title: COMBINATION FILTER/CARTRIDGE ASSEMBLY



(57) Abrégé/Abstract:

A filter cartridge assembly including a replendam that combines a particulate filter with an irregular shaped gas sorbent bed. Best operational practice requires that the air passing through the filter be distributed uniformly over the sorbent bed. The replendam directs the air over the surface of the larger sorbent bed utilizing vane-like structures extending from the reticulated member providing for uniform distribution.

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
16 May 2002 (16.05.2002)

PCT

(10) International Publication Number  
**WO 02/38249 A2**

- (51) International Patent Classification<sup>7</sup>: **B01D 53/04**, 46/52, A62B 23/02
- (21) International Application Number: PCT/US01/51336
- (22) International Filing Date: 26 October 2001 (26.10.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/243,918 27 October 2000 (27.10.2000) US
- (71) Applicant: **SCOTT TECHNOLOGIES, INC.** [US/US];  
One Chagrin Highlands, 2000 Auburn Drive, Suite 400,  
Beachwood, OH 44122 (US).
- (72) Inventor: **ESTKOWSKI, Christopher, G.**; 6015 105th  
Avenue, Pullman, MI 49450 (US).
- (74) Agents: **LINIHAN, Martin, G.** et al.; Hodgson Russ LLP,  
One M & T Plaza, Suite 2000, Buffalo, NY 14203-2391  
(US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**  
*without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: COMBINATION FILTER/CARTRIDGE ASSEMBLY



(57) Abstract: A filter cartridge assembly including a replendam that combines a particulate filter with an irregular shaped gas sorbent bed. Best operational practice requires that the air passing through the filter be distributed uniformly over the sorbent bed. The replendam directs the air over the surface of the larger sorbent bed utilizing vane-like structures extending from the reticulated member providing for uniform distribution.

WO 02/38249 A2

5

**COMBINATION FILTER/CARTRIDGE ASSEMBLY**CROSS-REFERENCE TO RELATED APPLICATION

Applicant hereby claims priority based on U.S. Provisional Application No. 60/243,918 filed October 27, 2000, entitled "Combination Filter/Cartridge Assembly," which is incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to air-purifying filter cartridge assemblies and in particular to a combination filter/cartridge assembly containing a particulate filter media in series arrangement with a sorbent bed.

20 BACKGROUND OF THE INVENTION

Cartridge filtering assemblies have been described previously in the art. One such assembly U.S. Patent No. 4,548,626 to Ackley, discloses a combination of a radially pleated filter and a sorbent bed. This invention does not disclose a support between the round filter and the sorbent bed having radially directed vanes for distributing air over the sorbent bed. Thus, the airflow through the sorbent bed may be short circuited and cause premature exhaustion of the bed.

U.S. Patent No. 6,044,842 to Pereira et al., discloses a gasketless adapter for fastening two filter elements to one another. However, the geometrical structure of the arrangement of the first and second does not allow for full utilization of the filtering capability and may cause excessive pressure drop.

U.S. Patent No. 4,714,486 to Silverthorn, discloses a filter canister having a canister body with top and

- 2 -

5 bottom parts sealed together, a filter for particulate material sealed into the top part and a separate sorbent cartridge fitted into the bottom part of the body. The design of the prior air filter cannister does not allow for uniform air distribution throughout the plenum  
10 chamber between the first and second filters which is an undesirable attribute of the design.

Therefore, as can be seen from the prior art patents, there is a need for a novel filter cartridge assembly which can be used with one or more filter  
15 assemblies and thus provide for structure bed integrity and for uniform distribution of air throughout the assembly.

#### SUMMARY OF THE INVENTION

20 The present invention meets the above-described need by providing a housing that combines with a particulate filter having an irregular shaped gas sorbent bed. Proper usage of the filter cartridge requires that the air passing through the filter be  
25 distributed uniformly over the sorbent bed. Thus, the filter cartridge directs the air radially over the surface of the sorbent bed utilizing the vane-like structures radiating out from the reticulated members. A multi-functional assembly located within the filter  
30 housing has been named a replendam. The term "replendam" is an acronym for an assembly which is a retention screen, a plenum chamber, and an adhesive barrier for a particulate filter.

As a retention screen, it provides stability to the  
35 sorbent bed to ensure individual grains of sorbent do

- 3 -

5 not move or otherwise shift in the sorbent column.  
Errant settling or shifting of the sorbent changes the  
flow characteristics of the bed and effects essential  
residence time of the gases that the bed must absorb.

As a plenum chamber, it ensures that the face  
10 velocity across the sorbent bed is uniform.

As an adhesive barrier, it prevents migration of  
glue into the plenum when the particulate filter is  
potted in place. Since the immobilization screen must  
apply pressure evenly, the adhesive barrier must be  
15 designed to allow a cushion so the filter area under it  
is not crushed.

The foregoing and additional advantages and  
characterizing features of the present invention will  
become clearly apparent upon reading of the following  
20 detailed description together with the included  
drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of the combination  
25 filter/cartridge assembly of the present invention.

Fig. 2 is a side elevational view of the  
combination filter/cartridge assembly of Fig. 1.

30 Fig. 3 is a partially cutaway side elevational view  
of the combination filter/cartridge assembly.

Fig. 4 is a detailed partial view of the  
combination filter/cartridge assembly shown in Fig. 3.

35

- 4 -

5           Fig. 5 is a detailed partial view of the  
combination filter/cartridge assembly shown in Fig. 3.

Fig. 6 is a perspective view of the replendam.

10           Fig. 7 is a bottom plan view of the replendam.

Fig. 8 is a cross-sectional view taken along line  
8-8 of Fig. 7.

15           Fig. 9 is a cross-sectional view taken along line  
9-9 of Fig. 7.

Fig. 10 is a detailed partial view from Fig. 9.

20           Fig. 11 is a perspective view of the cover.

Fig. 12 is a top plan view of the cover.

Fig. 13 is a side elevation view of the cover.

25

Fig. 14 is a bottom plan view of the cover.

Fig. 15 is a sectional side elevational view of the  
cover.

30

Fig. 16 is a detailed partial sectional view of the  
cover.

Fig. 17 is a perspective view of the body.

35

- 5 -

5           Fig. 18 is a top plan view of the body.

          Fig. 19 is a sectional side elevational view of the body.

10           Fig. 20 is a bottom plan view of the body with the reticulated wall removed for clarity.

          Fig. 21 is a top plan view of an alternate embodiment of the present invention.

15

          Fig. 22 is a side elevational view of an alternate embodiment of the present invention.

          Fig. 23 is an alternate embodiment of the cover of  
20 the present invention.

#### DETAILED DESCRIPTION

Now, referring to Figs. 1-23 generally and initially to Fig. 1, a combination cartridge/filter  
25 assembly 10 of the present invention is shown. The assembly 10 includes a particulate filter media 13 (Fig. 4) and a sorbent bed 16 (Fig. 4). The sorbent bed 16 is formed out of a sorbent media 17 that may include carbon materials comprising impregnated carbon and/or activated  
30 carbon. Other granular sorbent materials may also be suitable. Also, any materials that are air permeable and that are capable of absorbing or reacting with the gas contaminants to be removed or neutralized would also be suitable. The filter media 13 and the sorbent bed 16  
35 are disposed in a series arrangement with a relatively



- 6 -

5 small plenum chamber disposed between the filter media 13 and the sorbent bed 16 as will be described herein. The assembly 10 comprises a cover 19 that snaps onto a body 22. The cover 19 includes a grill or reticulated wall 23 spanning an opening 24. The filter media 13  
10 fits inside the cover 19 and is separated from the sorbent bed 16 by a replendam 25 (Figs. 4 and 6-10) as described below. The cover 19, body 22, and replendam 25 are formed out of suitable thermoplastic materials in injection molding processes or the like. Other  
15 materials having suitable properties for use as a filter cartridge and replendam may also be used.

In Fig. 2, the cover 19 has an air inlet 28 where ambient air is drawn into the assembly 10 for purification. The assembly 10 is suitable for use with  
20 a respiratory mask of the type disclosed in U.S. Patent No. 6,016,804 which is assigned to the assignee of the present invention and which is incorporated herein by reference. The outlet 31 of assembly 10 attaches to the inlet of a respiratory mask.

25 Turning now to Fig. 3, the path for the flow of air is indicated by arrows 34 and 37. The particulate filter media 13 is a round pleated filter media. Other particulate filters may also be suitable and other shapes of filters may also be suitable. The body 22 for  
30 the sorbent bed 16 is significantly larger than the filter media 13 and has an irregular six-sided shape. However, the number of sides and the shape of the sorbent bed 16 is not critical.

In Fig. 4, the cover 19 houses the particulate  
35 filter media 13 which as described above is typically a

- 7 -

5 round pleated filter media. The pleated filter media 13 is potted in the cover 19 as will be described in detail hereinafter. The inside of the cover 19 in cooperation with the bottom surface of the media 13, the replendam 25, and the top of the sorbent bed 16 forms a plenum  
10 chamber 40 between the filter media 13 and the sorbent bed 16 which is located in body 22. The replendam 25 maintains separation between the filter media 13 and the sorbent bed 16 to form plenum chamber 40. Also, the replendam 25 applies pressure to immobilize the sorbent  
15 bed 16 when the cover 19 is snapped onto the body 22 as will be described in detail hereinafter. In part, the immobilizing pressure is applied through a plurality of plastic springs 41 which will be described in detail hereinafter. The replendam 25 engages with a retention  
20 filter media 43 disposed over the sorbent media 17. The last layer inside the body 22 is a second retention filter media 49, which is preferably a fines filter that may be placed in the bottom of the body 22 or attached to the bottom of the body 22 by sonic welding, glueing,  
25 or other process.

As shown in Fig. 4, the perimeter of the replendam 25 has a V-shaped rib 50 extending downward toward the sorbent bed. Above the V-shaped rib 50, the replendam 25 has a V-shaped groove 53 disposed therein. A  
30 corresponding V-shaped rib 56 disposed on the cover 19 engages with the groove 53 when the cover 19 is snapped onto the body 22. The cover 19 has a second V-shaped rib 59 that engages with a V-shaped groove 62 disposed in the upper edge of the side wall 65 of the body 22.  
35 The cover 19 also includes a hook portion 68 (best shown

- 8 -

5 in Figs. 5 and 16) that snaps over a shoulder 71 (best shown in Fig. 19) formed in the outside top of the side wall 65 of the body 22.

Turning to Fig. 5, a sealing compound 74 is applied in a bead to the area around the V-shaped rib 59 to seal  
10 the joint where the rib 59 engages with the groove 62 (Fig. 4) in the body 22.

In Figs. 6-10, the replendam 25 includes a grill or reticulated wall 80 that is round to correspond to the shape of the filter media 13. Other shapes for  
15 different shaped filter media would also be suitable. An air dam 83 is disposed in substantially parallel and spaced apart relation above the reticulated wall 80. The air dam 83 is also round to correspond to the shape of the filter media 13, however, other shapes for non-  
20 round media would also be suitable. The air dam 83 acts as a adhesive barrier when the filter media 13 is potted in the cover 19 as described herein. Air dam 83 is attached to the reticulated wall 80 by a plurality of first inner legs 86 of the plurality of springs 41 (best  
25 shown in Fig. 10). In the embodiment shown, there are eight springs 41 that are approximately equidistant around the circumference of the reticulated wall 80. The springs 41 are U-shaped with the first legs generally designated as 86 being attached to the air dam  
30 83 and the second outer legs generally designated as 88 being attached to a circular inner support frame 89 (Fig. 7). The circular or round inner support frame 89 is disposed substantially coplanar with the reticulated wall 80. The inner support frame 89 is circular or  
35 round for the round filter media 13, however, it could

- 9 -

5 be other shapes for non-round media. As best shown in Fig. 10, the outer frame 95 extends below the plane formed by the reticulated wall 80, the inner frame 89, and the support members 92 so that the outer frame 95 makes the initial contact with the retention filter  
10 media 43. The plurality of lateral support members 92 attach the inner support frame 89 to an outer frame 95 forming a second reticulated wall 93 that conforms to the six-sided shape of the body 22. A plurality of vane-like members generally designated as 100 extend  
15 from the center of the reticulated wall 80 and connect between the inner support frame 89 and the outer frame 95. As shown the vane-like members 100 extend radially in substantially straight lines. For non-round filter media, the vane-like members 100 may be straight or  
20 curved depending on the filter geometry and may or may not extend radially. The vane-like members 100 extend vertically above the support members 92 between the horizontal planes defined by the reticulated wall 80 and the air dam 83. The vane-like members 100 are connected  
25 by a pair of curved members 101, 102 that are concentric with the inner frame member 89. The vanes 100 direct the air flow and also function as stiffening ribs for applications where sorbent bed immobilization is required so that energy can be transferred through the  
30 springs 41 across the replendam 25.

In Fig. 10, the V-shaped rib 50 and the V-shaped groove 53 of the replendam 25 are shown with relation to one of the springs 41 located at the side of the replendam 25. The first leg 86 of the spring 41 extends  
35 to the reticulated wall 80 and the second leg 88 extends

- 10 -

5 to the inner support frame 89. A short lateral support member 92 connects the inner support frame 89 to the outer frame 95. As described above the outer frame 95 conforms to the six-sided shape of the sorbent bed 16. The outer frame 95 is formed with the V-shaped rib 50 on  
10 the bottom and with the V-shaped groove 53 on the top.

In Figs. 11-16, the cover 19 is shown in greater detail. The cover 19 has a complex shape with a round section 110 extending outward from a six-sided planar section 113. The round section 110 corresponds to the  
15 shape of round filter media 13. Other shapes for section 110 for use with non-round filters would also be suitable. The six-sided planar section 113 terminates in side walls 115 that extend substantially perpendicular to the planar section 113. In Fig. 12,  
20 the opening 24 is covered by the grill or reticulated wall 23.

The round filter media 13 (Fig. 4) is potted in the round section 110 by applying a glue 111 (best shown in Fig. 4) to the perimeter of the filter media 13 such  
25 that air is prevented from passing around the edges of the filter media 13 between the media 13 and the inner wall of the cover 19. As shown in Fig. 4, the air dam 83 acts as a adhesive barrier to prevent glue from entering the plenum chamber 40.

30 In Fig. 16, the hook 68 and the first and second V-shaped ribs 56, 59 are shown in greater detail. Also shown is an inner wall 116 that extends downward for a short distance and surrounds the round section 110 for the round filter media 13. As shown in Fig. 15, the  
35 wall 116 has openings generally designated as 117

- 11 -

5 defined therein that are sized to receive the springs 41 that extend toward the air dam 83 when the replendam 25 is installed in the cartridge assembly 10. When the replendam 25 is installed in the assembly 10, the air dam 83 fits inside the inner wall 116, and the V-shaped  
10 groove 53 in the replendam 25 engages with the first rib 56 (best shown in Fig. 4).

Figs. 17-20, illustrate the body 22 in greater detail. The body 22 has a set of ribs generally designated as 120 disposed on a bottom surface 123. The  
15 ribs 120 are designed to channel the air flow toward the outlet and to assist in the immobilization of the sorbent materials 46. The bottom surface 123 is substantially planar and is shaped in a six-sided shape. Other shapes may also be suitable. The bottom surface  
20 123 is bordered by a plurality of side walls 65 that extend substantially perpendicular to the bottom surface 123 to form a chamber.

In Fig. 18, the outlet 31 has a grill or  
25 reticulated wall 140 that supports the sorbent bed 16. Turning now to Fig. 19, the body 22 has an opening 145 that is disposed in spaced apart relation to the reticulated wall 140. The opening 145 has a pair of truncated sides 148 that provide for inserting a  
30 quarter-turn bayonet mount adapter such as disclosed in U.S. Patent No. 6,016,804 through the opening. The space between the opening 145 and the reticulated wall 140 provides clearance for the adapter on the respiratory mask to fit inside the cartridge assembly 10  
35 and to turn into a locked position.

- 12 -

5           As shown in Fig. 19, the side walls 65 have  
shoulder 71 extending around the periphery of the top  
edge 133 of the side walls 65. As described above, the  
shoulder 71 cooperates with the hook 68 on the cover to  
provide for a snap-fit.

10           In Fig. 20, the opening 145 is shown with the  
reticulated wall 140 removed such that the sides 148 are  
clearly shown. The opening 145 is designed with sides  
148 such that the assembly 10 is capable of mounting  
onto a respiratory mask by means of a quarter turn  
15 bayonet adaptor of the type disclosed in U.S. Patent No.  
6,016,804.

          In operation, the combination filter/cartridge  
assembly 10 performs several functions. Returning to  
Fig. 4, the replendam 25 serves several functions.  
20 First, the replendam 25 is sized such that the bottom  
surface provides an immobilization force when the cover  
19 is snapped onto the body 22. When the cover 19 is  
snapped onto the body 22, the bottom of the round filter  
media 13 engages with the air dam 83 to provide a  
25 downward force against the sorbent bed 16. The force is  
transmitted through the springs 41 to the entire bottom  
surface of the replendam 25 such that an immobilization  
force is applied throughout the bottom surface of the  
replendam 25 onto the top surface of the sorbent bed 16.  
30 Also, the rib 50 disposed around the perimeter of the  
replendam 25 is forced downward onto the retention  
filter 43 when the cover 19 is snapped onto the body 22.  
The rib 50 provides a knife edge engagement with the  
retention filter media 43 that holds the media 43 in  
35 position.

- 13 -

5           Accordingly, the force of the replendam 25 on the top of the sorbent bed 16 promotes sorbent pack density and stability. As known to those of ordinary skill in the art, the settling or shifting of sorbent changes the flow characteristics of the bed and effects residence  
10       time of the gases that the bed must absorb.

          In addition to transmitting force to the bottom surface of the replendam 25 through the springs 41, the air dam 83 also provides a adhesive barrier to prevent the glue that is used to pot the filter media 13 in the  
15       cover 19 from entering the plenum chamber 40.

          Returning to Fig. 7, the design of the replendam 25 also promotes uniform distribution of air over the sorbent bed 16. The plenum 40 is designed to provide a chamber where equalization of the air flow can occur  
20       prior to entry of the air into the sorbent bed 16 such that the sorbent bed 16 surface uniformly receives air having the same or approximately the same face velocity. Uneven distribution of airflow will underutilize the sorbent bed 16 and decrease the bed life. Also, the  
25       radial vane-like structures 100 of the replendam 25 direct the air flow in the plenum chamber 40 over the entire surface of the sorbent bed 16 to promote uniform distribution of air flow across the bed.

          The embodiment shown in Figs. 1-20 provides a  
30       replendam 25 for use between filter media 13 and sorbent bed 16. However, the replendam 25 of the present invention could also be disposed between two different sized filter media or a multi-stage cartridge could be constructed with more than one replendam 25 disposed in  
35       combination with filter media and/or sorbent beds.



- 14 -

5           Also, the springs 41 may be utilized in a single stage filtering system such that the device would not include the vanes 100 and the plenum chamber 40. For example in an alternate embodiment shown in Fig. 21, the springs 41 could engage with an alternate cover 200  
10 (Fig. 23) such that the springs 41 could be used to transmit a force from the cover 200 to the retention filter 43 through the outer frame 95 and the reticulated structure 201 above the sorbent bed 16. The cover 200 has an irregular-shaped opening. As an alternative, the  
15 cover 200 could be provided with a round, smaller opening such as the opening covered by a reticulated wall shown in Fig. 11. Accordingly, the smaller round opening would facilitate an easy negative pressure check by the user of the device who would be able to cover the  
20 opening with one hand.

          In certain applications the force on the sorbent bed transmitted through the springs 41 to the replendam 25 may not be required. These applications may include situations where the replendam 25 is disposed between  
25 two filters or if the sorbent does not require the force on the top of the bed.

          Also, in another alternate embodiment for forming a plenum, an alternate replendam 300 shown in Fig. 22 could be constructed without plastic springs generally  
30 designated as 41. The replendam 300 could have the adhesive barrier air dam 83 connected to the inner support member 92 by means of a solid member 303 without spring properties. Accordingly, the springs 41 and the design of the replendam 25 may or may not be used in  
35 combination depending on the application.

- 15 -

5           While the invention has been described in  
connection with certain embodiments, it is not intended  
to limit the scope of the invention to the particular  
forms set forth, but, on the contrary, it is intended to  
cover such alternatives, modifications, and equivalents  
10 as may be included within the spirit and scope of the  
invention.

- 16 -

## 5 WHAT IS CLAIMED:

1. A replendam, comprising:
  - a first reticulated wall having a perimeter;
  - a second reticulated wall disposed about at least a  
10 portion of the perimeter of the first reticulated wall,  
the second reticulated wall having a plurality of vanes  
supported thereon, the second reticulated wall extending  
to an outer frame; and,
    - an air dam disposed in spaced apart relation to the  
15 first reticulated wall.
2. The replendam of Claim 1, wherein the air dam is  
attached to the first reticulated wall and to the second  
reticulated wall.  
20
3. The replendam of Claim 2, wherein the air dam is  
attached to the first and second reticulated walls by a  
spring having a first leg attached to the first  
reticulated wall and having a second leg attached to the  
25 second reticulated wall.
4. The replendam of Claim 1, wherein the first  
reticulated wall is round.
- 30 5. The replendam of Claim 4, wherein the plurality of  
vanes extend from the perimeter of the first reticulated  
wall.
6. The replendam of Claim 1, wherein the outer frame  
35 has a groove disposed on a first side.

- 17 -

5

7. The replendam of Claim 6, wherein the groove is V-shaped.

8. The replendam of Claim 1, wherein the outer frame  
10 has a sealing edge disposed on the side opposite from the air dam.

9. A replendam, comprising:  
a first reticulated wall having a perimeter;  
15 a second reticulated wall disposed about at least a portion of the perimeter of the first reticulated wall, the second reticulated wall having a plurality of vanes supported thereon, the plurality of vanes extending from the perimeter of the first reticulated wall, the second  
20 reticulated wall extending to an outer frame, the outer frame having a sealing edge disposed thereon; and,  
an air dam disposed in spaced apart relation to the first reticulated wall and connected to the first and second reticulated walls.

25

10. The replendam of Claim 9, wherein the first reticulated wall is round.

11. The replendam of Claim 9, wherein the air dam is  
30 connected to the first and second reticulated walls by a spring having a first leg attached to the first reticulated wall and having a second leg attached to the second reticulated wall.

35 12. The replendam of Claim 9, wherein the outer frame

- 18 -

5 has a groove disposed on a first side.

13. A filter cartridge assembly, comprising:

a cover having a recessed portion with an opening  
at a first end covered by a reticulated wall, the  
10 recessed portion capable of receiving filter media, the  
cover having a planar wall disposed adjacent to the  
recessed portion and a rim;

filter media disposed inside the recessed portion  
of the cover;

15 a cartridge body having side walls and a bottom  
wall with an opening defined therein;

a sorbent media bed disposed inside the cartridge  
body; and,

a replendam having a first reticulated wall having  
20 a perimeter, a second reticulated wall disposed about at  
least a portion of the perimeter of the first  
reticulated wall, the second reticulated wall having a  
plurality of vanes supported thereon, the second  
reticulated wall extending to an outer frame, and, an  
25 air dam disposed in spaced apart relation to the first  
reticulated wall, the replendam disposed between the  
cover and the cartridge body such that the air dam  
engages with the filter media, the bottom of the  
replendam engages with the sorbent media bed, and the  
30 replendam defines a plenum chamber between the filter  
media and the sorbent media bed.

14. The filter cartridge assembly of Claim 13, wherein  
the air dam is connected to the first reticulated wall  
35 and to the second reticulated wall.

- 19 -

5

15. The filter cartridge assembly of Claim 14, wherein the air dam is connected by a spring having a first leg attached to the first reticulated wall and having a second leg attached to the second reticulated wall.

10

16. The filter cartridge assembly of Claim 13, wherein the first reticulated wall is round.

17. The filter cartridge assembly of Claim 16, wherein  
15 the plurality of vanes extend radially from the perimeter of the first reticulated wall.

18. The filter cartridge assembly of Claim 13, wherein the outer frame has a groove disposed on a first side.

20

19. The filter cartridge assembly of Claim 18, wherein the groove is V-shaped.

20. The filter cartridge assembly of Claim 19, wherein  
25 the cover has a rib that engages with the groove on the outer frame of the replendam.

21. The filter cartridge assembly of Claim 1, wherein the outer frame has a sealing edge.

30

22. A single stage filter assembly, comprising:  
a cover having a planar wall disposed adjacent to an outer rim;

a retaining member including a reticulated wall  
35 bordered by an outer frame, the retaining member having

- 20 -

5 a plurality of springs disposed thereon;  
a cartridge body having side walls and a bottom  
wall with an opening defined therein; and,  
a sorbent media bed disposed inside the cartridge  
body.

10

23. The filter assembly of Claim 22, wherein the  
springs are integrally formed in the retaining member.

24. The filter assembly of Claim 22, wherein the cover  
15 has an opening sized such that it can be covered by a  
hand of a user.

25. The filter assembly of Claim 22, wherein the  
retaining member further comprises a plurality of vane-  
20 like members for directing the air flow.

FIG. 1





FIG. 5






FIG. 2










FIG. 7






FIG. 11




FIG. 12

FIG. 13





FIG. 14







FIG. 18




FIG. 20






FIG. 19










FIG. 22




FIG. 23